

EXTRA-RV 80



APPLICATION

For corded and cordless drills with and without spindle stop up to a maximum torque of 100 Nm and up to 1500 watt.

TYPE

Impact-resistant quick-action drill chuck with radial locking and plastic or metal sleeve.
Available in two and single sleeve design for machines with and without spindle stop.
With through-hole for clockwise and counterclockwise rotation.

CUSTOMER BENEFITS

- Easy clamping and locking with one manual operation for maximum user-friendliness
- No re-clamping in clockwise and counterclockwise rotation due to radial locking
- Impact-resistant for universal use

TECHNICAL FEATURES


- With carbide inserts in the clamping jaws (size 13)



A01
EXTRA-RV 80 with radial locking, metal design




Item no.	Size	Clamping capacity mm	Mount	Retaining ring	Design	Concentricity deviation max. mm	External Ø mm	Length opened mm	Length closed mm	Max. mach. capacity	Through-hole
893351	10	1-10	3/8"-24		metal	0,35	42,7	55	60,9	550	●
893350	10	1-10	1/2"-20		metal	0,35	42,7	55	60,9	550	●
1033053	10	1-10	1/2"-20	●	metal	0,35	42,7	55	60,9	550	●
1033051	13	1,5-13	3/8"-24	●	metal	0,4	42,7	64,5	72,4	1100	●
893352	13	1,5-13	1/2"-20		metal	0,4	42,7	64,5	72,4	1100	●
802490	13	1,5-13	1/2"-20	●	metal	0,4	42,7	64,5	72,4	1100	●



A01
EXTRA-RV 80 with radial locking, plastic design



Item no.	Size	Clamping capacity mm	Mount	Retaining ring	Design	Concentricity deviation max. mm	External Ø mm	Length opened mm	Length closed mm	Max. mach. capacity	Through-hole
767573	10	1-10	3/8"-24		plastic	0,35	42,7	55	60,9	550	●
664467	10	1-10	3/8"-24	●	plastic	0,35	42,7	55	60,9	550	●
767651	10	1-10	1/2"-20		plastic	0,35	42,7	55	60,9	550	●
767639	10	1-10	1/2"-20	●	plastic	0,35	42,7	55	60,9	550	●
767641	13	1,5-13	3/8"-24		plastic	0,4	42,7	64,5	72,4	1000	●
767657	13	1,5-13	3/8"-24	●	plastic	0,4	42,7	64,5	72,4	1000	●
767580	13	1,5-13	1/2"-20		plastic	0,4	42,7	64,5	72,4	1000	●
767692	13	1,5-13	1/2"-20	●	plastic	0,4	42,7	64,5	72,4	1000	●



EXTRA-RV 80

A01

EXTRA-RV 80 with SDS plus mounting shank and radial locking, metal design



Item no.	Size	Clamping capacity mm	Mount	Retaining ring	Design	External Ø mm	Length opened mm	Length closed mm	Through-hole
1288566	13	1,5-13	1/2"-20 / SDS plus	•	metal	42,5	64,5	72,4	•

Use exclusively with hammer function deactivated



A01

EXTRA-RV 80 for impact screwdriver mounting 1/4" Hex, plastic design, specially suited for impact screwdrivers (eccentricity)



Item no.	Size	Clamping capacity mm	Mount	Retaining ring	Design	External Ø mm	Length opened mm	Length closed mm	Through-hole
1178269	10	1-10	1/4"-Hex		plastic	42,5	55	63,1	

