

SUPRA-I



APPLICATION

Especially suitable on stationary drilling machines and hand-operated drills. Rapid clamping and releasing of the drilling tools without key.

TYPE

Self-clamping flat jaw drill chuck with metal sleeve. Industrial design with maximum precision.

CUSTOMER BENEFITS


- ⊕ Highest concentricity of up to 0.12 mm
- ⊕ Increase in the clamping force proportional to the cutting force by the automatic reclamping function
- ⊕ Light and quick clamping of tools for maximum user-friendliness

TECHNICAL FEATURES

- Strong retaining ring
- Functional components made from steel
- All wear parts are hardened and ground
- Only suitable for clockwise rotation



A02
SUPRA-I heavy industrial version for stationary drilling machines and hand-operated drills



Item no.	Size	Type	Clamping capacity mm	Mount	Concentricity deviation max. mm	External Ø mm	Length opened mm	Length closed mm	Weight g
871020	4	I	0-4	J0	0,12	26	46,5	51,5	130
871019	4	I	0-4	B10	0,12	26	45,5	50,8	137
871025	6	I	0-6,5	3/8"-24	0,2	32	59,5	65,6	301
871024	6	I	0-6,5	J1	0,12	32	59,5	65,6	275
871022	6	I	0-6,5	B10	0,12	32	59,5	65,6	280
871023	6	I	0-6,5	B12	0,12	32	59,5	65,6	250
871033	8	I	0-8	J1	0,12	35,8	67	73,4	390
871034	8	I	0-8	3/8"-24	0,2	35,8	67	73,4	390
871031	8	I	0-8	B10	0,12	35	67	73,5	380
871032	8	I	0-8	B12	0,12	35,8	67	73,4	345
871042	10	I	0-10	J2	0,12	40,2	80,5	87,1	636
871043	10	I	0-10	J33	0,12	40,2	84	90,6	560
871045	10	I	0-10	1/2"-20	0,2	40,2	79,5	86,1	618
871044	10	I	0-10	3/8"-24	0,2	40,2	79,5	86,1	625
871040	10	I	0-10	B12	0,12	40,2	79,5	86,1	578
871041	10	I	0-10	B16	0,12	40,2	82,5	89,1	624
871055	13	I	1-13	1/2"-20	0,2	46	93	101,5	932
871052	13	I	1-13	J2	0,12	46	91	99,5	900
871054	13	I	1-13	J6	0,12	46	94	102,5	870
871051	13	I	1-13	B16	0,12	46	93	101,5	915
871053	13	I	1-13	J33	0,12	46	94	102,5	948
871066	16	I	3-16	J6	0,12	51	96,5	106,8	1120
871064	16	I	3-16	B16	0,12	51	96,5	106,8	1161
871065 ¹⁾	16	I	3-16	B18	0,12	51	96,5	106,8	1115

¹⁾ shortened: B18 by 7 mm